


NOTES:

A. TO BE USED WITH SOUTHCO STANDARD R4-30 LATCH SERIES.

B. MOUNTING TORQUE FOR STRIKER INSTALLATION SHOULD BE 25-30 Nm.

REVISION HISTORY			
REV	DATE	BY	DESCRIPTION
D	09OCT2015	MJS/CMK	PRN: P2015-2045



3	-	1	O-RING	70 DUROMETER BUNA N	NATURAL	STAINLESS STEEL BOLT
2	-	1	WASHER	STAINLESS STEEL	ANNEALED	
1	-	1	BOLT	STAINLESS STEEL	ANNEALED	
-	R4-90-321-20	-	STRIKER BOLT ASSEMBLY	-	-	
3	-	1	O-RING	70 DUROMETER BUNA N	NATURAL	STEEL BOLT
2	-	1	WASHER	STAINLESS STEEL	ANNEALED	
1	-	1	BOLT	STEEL	ZINC BRIGHT CHROMATE	
-	R4-90-321-10	-	STRIKER BOLT ASSEMBLY	-	-	
NO.	PART NUMBER	QTY	TYPE OF COMPONENT	MATERIAL	FINISH	GENERAL NOTES

THIRD ANGLE PROJECTION		 CONNECT • CREATE • INNOVATE	
INCHES [MM]			
SURFACE AREA		DESCRIPTION	
VOLUME		R4 STRIKER BOLT ASSEMBLY	
PROPRIETARY ITEM <small>EXCEPT FOR USES EXPRESSLY GRANTED IN WRITING, INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS, PATENT AND OTHERWISE, ARE RESERVED BY SOUTHCO, INC.</small>		SIZE	DWG NO.
PER ASME Y14.5M-1994		A NX	J-R4-90-321
		DRAWN BY	SHEET
		ACH/MJS	1 OF 1
		DATE	SCALE
		02JUL2009	1:1