

**southco**

PROPRIETARY ITEM - EXCEPT FOR USES EXPRESSLY GRANTED IN WRITING, INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS, PATENT AND OTHERWISE ARE RESERVED BY SOUTHCO, INC.

C5 SEALED LEVER LATCH

DATE	DRAWN	CHKD	SCALE	DRAWING NUMBER
19JUN92	JGK		0.75:1	J-C5-3

NOTES:


- A. MATERIAL AND FINISH:
- HOUSING, HANDLE, AND BUTTON: DIE CAST ZINC, BLACK POWDER COAT WITH STEEL HARDWARE
  - LEVER AND CRANK: DIE CAST ZINC, CLEAR CHEMICAL PROTECTIVE FILM
  - TORSION SPRING: 302 STAINLESS STEEL, PASSIVATED
  - ROLL PIN: 420 STAINLESS STEEL, PASSIVATED
  - O-RING: BUNA-N, NATURAL
  - ADJUSTING SCREW, JAM NUT, MOUNTING BRACKET AND SCREW: 1010 STEEL, ZINC PLATE CHROMATE PLUS SEALER

PANEL THICKNESS (mm)	LONG LEVER GRIP RANGE *	ASSEMBLY PART NUMBER
1-11	29-45	C5-11-35
11-21		C5-12-35
21-31		C5-13-35
31-41		C5-14-35

REV	DATE	DRAWN/CHKD	DESCRIPTION
F	01JUN2006	MDY/MJS	PRN: P2006-0752
G	17MAY2022	CMS/JDC	PRN: P2022-0882

**MILLIMETERS**

ALL DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.



THIRD ANGLE PROJECTION

A3 PAPER SIZE

\*SHORT LEVER GRIP RANGE AVAILABLE FROM 1 TO 14 MILLIMETERS, REFERENCE DRAWING NUMBER J-C5-1

\*MEDIUM LEVER GRIP RANGE AVAILABLE FROM 14 TO 29 MILLIMETERS, REFERENCE DRAWING NUMBER J-C5-2

